

FIG. 1

40 →




FIG. 2
(PRIOR ART)




FIG. 5




FIG. 6

FIG. 7






FIG. 7






FIG. 10




FIG. 11

FIG. 12




FIG. 12

FIG. 13

FIG. 14

FIG. 15




FIG. 16




FIG. 17




FIG. 18





FIG. 19






FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25

FIG. 26





FIG. 27






FIG. 28A

904, cont.

- THE CONDUCTORS CAN BE OF ANY SUITABLE TYPE, SUCH AS SURFACE TRACES, PADS, OR BARS
- THE ONE OR MORE CAPACITORS AND/OR CAPACITOR ASSEMBLIES ARE ARRANGED SUCH THAT CERTAIN TERMINALS OF THE FIRST POLARITY TYPE CONTACT THE FIRST SET OF CONDUCTORS, AND CERTAIN TERMINALS OF THE SECOND POLARITY TYPE CONTACT THE SECOND SET OF CONDUCTORS
- IF THE IC PACKAGE SUBSTRATE SURFACE [ALTERNATIVE EMBODIMENT: IC SURFACE] HAS CONDUCTIVE BARS, ONE OR MORE OF THE CAPACITORS AND/OR CAPACITOR ASSEMBLIES IS POSITIONED BETWEEN ADJACENT ONES OF THE BARS

906)

SECURE THE CAPACITORS AND/OR CAPACITOR ASSEMBLIES TO THE SUBSTRATE SURFACE [ALTERNATIVE EMBODIMENT: TO THE IC SURFACE] USING A SUITABLE MECHANISM

- E.G., APPLY A FILL OR ADHESIVE MATERIAL TO THE CAPACITORS AND/OR CAPACITOR ASSEMBLIES, AND/OR TO OPENINGS BETWEEN THE CAPACITORS AND/OR CAPACITOR ASSEMBLIES; USE SPACERS OR CLAMPS; ETC.

908)

POSITION AND MOUNT AN IC ON THE MOUNTING REGION, E.G. USING SOLDER REFLOW

- ELECTRICALLY COUPLE THE IC TERMINALS TO CORRESPONDING TERMINALS OF THE ONE OR MORE CAPACITORS AND/OR CAPACITOR ASSEMBLIES, AND OPTIONALLY TO CONDUCTORS ON THE SUBSTRATE

FIG. 28B

908, cont.




FIG. 28C




FIG. 29A

958,



MOUNT THE IC ON AN IC MOUNTING REGION OF
THE IC PACKAGE SUBSTRATE

- FOR THE ONE EMBODIMENT: CONDUCTIVE BARS FROM THE FIRST SET AND SECOND SETS TOGETHER MAKE UP THE REQUIRED NUMBER OF CONDUCTIVE BARS
- FOR THE ALTERNATIVE EMBODIMENT: CONDUCTIVE BARS FROM THE FIRST SET OF CONDUCTIVE BARS ARE JOINED TO CONDUCTIVE BARS FROM THE SECOND SET OF CONDUCTIVE BARS TO FORM CONDUCTIVE BARS HAVING A FINAL DESIRED HEIGHT



960

END

FIG. 29B

11/17 2000